



SK-EM404

15-INCH PATIENT MONITOR



SK-EM404

FEATURES AND HIGHLIGHTS

Internal structure: It uses an aluminum-magnesium alloy stand, which is stable, reliable, has good shock resistance, and is easy to move.

Monitoring functions: Offers 6 comprehensive monitoring functions, covering various aspects: ECG (Electrocardiogram), heart rate (HR), respiration rate (RESP), blood oxygen level (SpO2), pulse rate (PR), non-invasive blood pressure (NIBP), and body temperature (TEMP).

Technical parameters

▪ Product weight	NW: 3.8kg
▪ Product size	305*160*287 mm
▪ ECG (Lead configuration)	6-pin, 5-lead ECG lead wires
▪ ECG (Gain)	'25, '50, '100, '200
▪ ECG (Heart rate range Adults)	15 bpm to 300 bpm
▪ ECG (Newborns/children)	15 bpm to 350 bpm
▪ ECG (Electrode polarization voltage range)	±300mV
▪ Respiration (Measurement method)	RA-LL (R-F) Impedance Method
▪ Respiration (Respiration rate range: Adults)	(0 -120) BrPM
▪ Respiration (Children and newborns)	(0-150) BrPM
▪ Respiration (Apnea alarm)	(10-40) seconds
▪ Measurement range of blood oxygen saturation	0~100%, resolution: 1%, accuracy: 70%~100%: ±2, 0% ~69%
▪ Measurement range of pulse rate	20 bpm to 300 bpm, with a resolution of 1 bpm and an accuracy of ±3 bpm
▪ Non-invasive blood pressure (Operating modes)	manual/automatic/continuous
▪ Non-invasive blood pressure (Pulse Rate Range)	(40 - 240) bpm
▪ Non-invasive blood pressure (Measurement range)	Systolic pressure (40-270) mmHg, diastolic pressure (10-215) mmHg, mean arterial pressure (20-235) mmHg
▪ Non-invasive blood pressure (Static pressure range)	(0-300) mmHg, static pressure accuracy: ±3 mmHg
▪ Body temperature , measurement Range	(0-50)°C, resolution: 0.1°C, accuracy



Other Features

Fanless design for a quiet, energy-efficient, and clean operation, providing comprehensive monitoring for adults, children, and newborns; Alarm event review, drug concentration calculation, and titration table functions; Built-in recorder for one-touch data printing; Multiple-channel synchronized ECG algorithm, supporting ST and ARR analysis functions, as well as abnormal ECG analysis; Analog SpO2 technology, resistant to motion interference, ambient light interference, and suitable for measurements during weak perfusion; Non-invasive blood pressure measurement options: manual, continuous, or interval measurement, with storage capacity for up to 400 sets of blood pressure data.

Design

Integrated design, streamlined functionality, stable performance, strong anti-interference capability, and long-lasting durability.

**Shell material**

Made from new ABS engineering plastic mold injection molding, which is more corrosion-resistant.

**Screen design**

15-inch high-brightness TFT color LCD display, black mirror design, the operation interface is user-friendly, and the data wave is clearly visible.

**Blood pressure button**

Conspicuous, independent blood pressure button for easy operation.

**Handle**

A concealed groove handle on the back, simple and stylish, comfortable to hold, stable, and easy to move.

**Alarm system**

Allows for the customization of different alarm levels with both audible and visual alerts.

**Power supply**

Utilizes high-performance power supply, wide voltage range from AC100V-240V, built-in rechargeable lithium battery, compatible with both AC and DC power sources, providing continuous power for over 2 hours.

**Operating interface**

Simultaneously displays ECG waveforms for channels 1 to 7, with the ability to show all 8 waveforms on the same screen, enabling cascading ECG waveform display. The interface supports both Chinese and English, featuring large font size for easy reading, and offers one-touch shuttle operation.

**Patient information input function**

Supports both wired and wireless networking capabilities.

**Interface settings**

USB and network interfaces facilitate the integration into a central monitoring system and enable the free exchange of information.





CONSTANT INNOVATION



Design



Research



Manufacturing



Maintenance



Service



WORLDWIDE BRANCHES

USA

Saikang Medical Technology, Inc.
17800 Castleton St Ste 180,
City of Industry, 91748, California.
Tel.: +1 949648 2776

United Kingdom

UK Healthward International Ltd.
Dept. 111, 196 High Road Wood
Green, N22 8HH, London.
Tel.: +44 2032399738

Russia

Saikang Medical Russia LLC
Truda 174,
454080 Chelyabinsk.
Tel.: +7 (351) 214 5566 / 8811 / 1516

East Africa

Saikang Medical Solutions Ltd.
Viraj Complex Unit 3, Mombasa
Road, P.O. Box 14262-00800, Nairobi.
Kenya.
Tel.: +254 733 704 690

Middle East

Saikang Medical Supplies LLC
X22-S03 England Cluster,
International City, Dubai.
United Arab Emirates.
Tel.: +20 128 8962497

SAIKANG / Medical

Jiangsu Saikang Medical Equipment Co., Ltd.
STOCK CODE: 870098

📍 No. 35, Lehong Road · Zhangjiagang (Jiangsu) · China
☎ +86 18021231901 · 🕒 24/7
✉ sales@chinasaikang.com
🌐 www.saikangmedical.com



Company video



General catalogue